

## **UN38.3 CERTIFICATE OF COMPLIANCE**

## UN MANUAL OF TESTS AND CRITERIA, PART III, Sub Section 38.3 Rev. 6 Lithium-Ion Rechargeable Batteries (ST/SG/AC.10/11/Rev. 6)

This is to certify that the following battery has been proven to comply with the requirements of the UN Manual of Tests and Criteria, Sixth Revised Edition, Part III sub-section 38.3 (Rev. 6). Lithium Batteries - (ST/SG/AC. 10/11/Rev. 6)

## Manufacturer

Name: Fedco Batteries A		Addre	Address: 1363 Capital Drive	
City: Fond du Lac	State: WI		Zip: 54936-1403	Country: USA
Phone: 920-922-6490	E-mail: info@fedcobatteries.com		Website: fedcobatteries.com	

**Test Laboratory** 

Name: Specialty Battery Group		Address: Rue Georges Leclance BP 1039			
City: Poitiers	State:		Zip: Cedex 09	Country: France	
Phone: 33-1-58-63-16-00	E-mail:		Website: saftbatteries.com		

**Battery Description** 

Stock Code No.: 4/LS14500	Product Description: 3.6V, 2.6Ah Lithium Battery (x4)	
Cell Manufacturer: Saft	Cell Part Number: LS14500	
Cell Configuration: 1S1P (x4)	Nominal Voltage: 3.6 V	
Nominal Capacity: 2.6 Ah	Nominal Watt-hour: 4.32 Wh	
Mass: 0.7 g of lithium	Date of Test Report: 1/9/2016	
Physical Description: 2.06 x .68 battery pack (x4)	Test Report ID: P0136-02, T0404-13	

## **TESTS AND RESULTS:**

Test Number Test Description		Requirements	Results	
38.3.4.1 (T-1)	Altitude Simulation	No mass loss, leakage, venting, rupture or fire. OCV >90% of value before the test.	Pass	
38.3.4.2 (T-2)	Thermal Cycling	No mass loss, leakage, venting, rupture or fire. OCV >90% of value before the test.	Pass	
38.3.4.3 (T-3)	Vibration	No mass loss, leakage, venting, rupture or fire. OCV >90% of value before the test.	Pass	
38.3.4.4 (T-4)	Shock	No mass loss, leakage, venting, rupture or fire. OCV >90% of value before the test.	Pass	
38.3.4.5 (T-5)	External Short Circuit	External Temperature <170°C.  No disassembly, rupture or fire within 6 hours of test.	Pass	
38.3.7.6 (T-6)	Impact	This test is for cells only.	N/A	
38.3.4.7 (T-7)	Overcharge	No disassembly or fire within 7 days of test. This test is for rechargeable batteries only.	Pass	
38.3.4.8 (T-8)	Forced Discharge	This test is for cells only	N/A	

Reviewed by:

Approved by:

Dong Milles Doug Miller Stephen P. Victor, Jr. Vice **Engineering Manager** Chairman & C.E.O. Date: 10/21/2020

Date: 10/21/2020